

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Please cancel claims 10, 18, 21 and 24 without prejudice.

Listing of Claims:

1. (Currently amended) An electrical connector comprising:

a connector housing; and

at least one deformable connector terminal arrangement disposed at the connector housing, the or each connector terminal arrangement comprising:

a terminal comprising a movable resilient arm portion, a contact portion at one end of the resilient arm portion for connecting to a first electrical point and a support portion connected to another end of the resilient arm portion and for connecting to a second electrical point, wherein the support portion is seated in the connector housing, and wherein the terminal further comprises a contact tail portion extending from the support portion out of the housing;

a first pivot portion for pivoting of the resilient arm portion relative to the support portion; and

a second pivot portion for pivoting of the contact portion relative to the resilient arm portion,

wherein the resilient arm portion is located directly opposite a base portion of the connector housing, and when the contact portion is pressed down towards the base portion, the resilient arm portion is configured to move towards the base portion and contact the base portion at the second pivot portion.

2. (Original) A connector according to claim 1, wherein the resilient arm portion is operable to deflect about the first pivot portion during movement of the contact portion in a first direction up to a first deflection position, and the contact portion is operable to deflect about the second pivot portion during further movement of the contact portion in the first direction beyond the first deflection position.

3. (Previously presented) A connector according to claim 1, wherein the first pivot portion connects the resilient arm portion to the support portion, the first pivot portion resiliently resists deflection of the resilient arm portion if a force is applied to the contact portion.

4. (Previously presented) A connector according to claim 1, wherein the resilient arm portion and the support portion are elongate.

5. (Previously presented) A connector according to claim 1, wherein the contact portion comprises a bent segment having an arched portion for contacting the first electrical point.

6. (Previously presented) A connector according to claim 1, wherein the terminal further comprises the first pivot

portion, disposed between the resilient arm portion and the support portion.

7. (Original) A connector according to claim 6, wherein the first pivot portion is formed integrally with the resilient arm portion and the support portion.

8. (Previously presented) A connector according to claim 6, wherein the first pivot portion comprises a resilient connecting portion connecting the resilient arm portion and the support portion.

9. (Previously presented) A connector according to claim 6, wherein the first pivot portion comprises a bend joining the resilient arm portion and the support portion.

10. (Cancelled)

11. (Previously presented) A connector according to claim 1, wherein the second pivot portion comprises a protuberance disposed on at least one of the terminal and the housing.

12. (Original) A connector according to claim 11, wherein the or each protuberance of a terminal arrangement has a rounded surface.

13. (Original) A connector according to claim 11, wherein the or each protuberance of a terminal arrangement has a flat surface.

14. (Previously presented) A connector according to claim 11, wherein the or each protuberance of a terminal arrangement is solid.

15. (Previously presented) A connector according to claim 11, wherein the or each protuberance of a terminal arrangement is hollow.

16. (Previously presented) A connector according to claim 1, wherein the terminal further comprises the second pivot portion, disposed between the resilient arm portion and the contact portion.

17. (Original) A connector according to claim 16, wherein the second pivot portion is formed integrally with the resilient arm portion.

18. (Cancelled)

19. (Previously presented) A connector according to claim 16, wherein the second pivot portion comprises a bent portion of the resilient arm portion.

20. (Original) A connector according to claim 19, wherein the bent portion is arcuate.

21. (Cancelled)

22. (Previously presented) A connector according to claim 1, wherein the second pivot portion is disposed on the housing.

23. (Previously presented) A connector according to claim 1, wherein the resilient arm portion is disposed at an angle with respect to the support portion.

24. (Cancelled)

25. (Previously presented) A connector according to claim 1, wherein the connector terminal is formed of an electrically conductive material.

26. (Currently amended) An electrical connector comprising:

a connector housing; and

at least one deformable connector terminal arrangement disposed at the connector housing, the or each connector terminal arrangement comprising:

a terminal comprising a movable resilient arm portion, a contact portion at one end of the resilient arm portion for connecting to a first electrical point and a support portion connected to another end of the resilient arm portion and for connecting to a second electrical point;

a first pivot portion for pivoting of the resilient arm portion relative to the support portion; and

a second pivot portion for pivoting of the contact portion relative to the resilient arm portion, wherein the connector housing is formed of an electrically insulating material,

wherein the resilient arm portion is located directly opposite a base portion of the connector housing, and when the contact portion is pressed down towards the base portion, the resilient arm portion is configured to move towards the base portion and contact the base portion at the second pivot portion.

27. (Previously presented) A connector according to claim 1, wherein the terminal is elongate, with the contact portion at an opposite end from the support portion.

28. (Previously presented) A connector according to claim 1, wherein the connector housing comprises one or more cavities, with individual ones of the connector terminal arrangements arranged in individual ones of the cavities.

29. (Original) A connector according to claim 28, further comprising separating walls between adjacent cavities.

30. (Previously presented) A connector according to claim 28, wherein individual cavities are defined by a roof portion spaced apart from a base portion, with the resilient arm portion and the support portion of a connector terminal arrangement disposed within the cavity.

31. (Previously presented) A connector according to claim 1, wherein the tail portion extending from a free end of the support arm portion, to contact the second electrical point.

32. (Previously presented) A connector according to claim 31 wherein the connector housing comprises one or more cavities, with individual ones of the connector terminal arrangements arranged in individual ones of the cavities, wherein the contact portions and the tail portions of the terminal protrude from individual cavities.

33. (Previously presented) A connector according to claim 31, wherein the tail portion comprises a first free end of the terminal.

34. (Previously presented) A connector according to claim 1, wherein the contact portion comprises a second free end of the terminal.

35. (Previously presented) A connector according to claim 1, wherein the housing further comprises a mounting pin for mounting the housing in an assembly.

36. (Previously presented) An assembly comprising:

a first circuit;

a second circuit; and

an electrical connector as in claim 1 electrically connecting the first circuit to the second circuit.

37. (Original) An assembly according to claim 36, wherein:

the connector is mounted to connect the first and second circuits electrically;

the first circuit comprises one or more first electrical points with which the one or more contact portions are in contact; and

the second circuit comprises one or more second electrical points with which the one or more support portions are in contact.

38. (Original) An assembly according to claim 37, wherein the one or more resilient arm portions are pivoted about the respective first pivot portions; and the one or more contact

portions are pivoted about the respective second pivot portions.

39. (Previously presented) An assembly according to claim 36, wherein the first circuit is a printed circuit board.

40. (Previously presented) An assembly according to claim 36, wherein the second circuit is a flex circuit.

41. (Previously presented) A method of connecting an assembly, which assembly is as defined in claim 36, the method comprising:

contacting one or more first electrical points of the first circuit with one or more contact portions of the connector;

contacting one or more second electrical points of the second circuit with one or more support arm portions of the connector;

moving the first circuit against a biasing force from the one or more contact portions of the connector, deflecting the resilient arm portion about the first pivot portion during movement of the contact portion in a first direction to a first deflection position, and deflecting the contact portion about the second pivot portion during further movement of the contact portion in the first direction beyond the first deflection position.

42. (Original) A method according to claim 41, further comprising mounting the connector to the second circuit prior moving the first circuit against the biasing force.

43. (Previously presented) A method according to claim 41, further comprising mounting the first circuit to the connector.

44. (Original) A method according to claim 43, wherein mounting the first circuit to the connector comprises moving the first circuit against the biasing force.

45. (Previously presented) A method according to claim 41, wherein moving the first circuit against the biasing force is achieved by screwing the first circuit down.